

EPS-2308

8-CH Relay Output Module



Features

- 8-CH relay output
- Quick removable European type connector
- Slave module healthy monitoring
- Wide operation temperature range: -20°C - 60°C
- Compact size: 100 (L) x 100 (H) mm
- IEC-61131 compliant

Ordering Information

- **EPS-2308**
8-CH Relay Output Module

Specifications

■ Power Consumption	1.9W
■ Hot Swap	Yes
■ Operating Temp.	-20-60 °C
■ Digital Output Channel	8 Relay Out
■ Output Type	Relay
■ Output Signal Capability (Contact Rating)	AC: 125V @ 0.5A DC: 30V @ 2A
■ Response Time	5mS
■ Self-Diagnostic	Power / Communication / WDT
■ Connector Type	Phoenix Contact DFMC

EPS-3216

16-CH 0-20mA Analog Input Module



Features

- 16-CH 100kS/s 0-20mA differential type analog input
- Quick removable European type connector
- Slave module healthy monitoring
- Wide operation temperature range: -20°C - 60°C
- Compact size: 100 (L) x 100 (H) mm
- IEC-61131 compliant

Ordering Information

- **EPS-3216**
16-CH 0-20mA Analog Input Module

Specifications

■ Power Consumption	2.5W
■ Hot Swap	Yes
■ Operating Temp.	-20-60 °C
■ Analog Input Channel	16
■ Input Type	Differential
■ Input Range	0 – 20mA
■ Offset Error	± 0.1mV
■ Gain Error	± 0.05% of FSR
■ Sampling rate	100KHz
■ Resolution	16 bit
■ Connector Type	Phoenix Contact DFMC