

# PXIS-2630

## 8-Slot 3U PXI/CompactPCI Chassis with 400 W AC Power Supply



### Introduction

Prepared for rugged mobility, the ADLINK PXIS-2630 series is a 3U PXI chassis with one system slot and seven peripheral slots. The chassis is compliant with PXI and CompactPCI specifications and accepts both PXI and CompactPCI modules. The PXIS-2630 integrates all PXI features, including a 10 MHz reference clock, start trigger, local bus, and trigger bus.

Reliable power is supplied to the PXIS-2630 chassis by an industrial-grade 400 W AC power supply. The status of system power supplies, temperature, and fan operations are monitored by a chassis-integrated alarm module. When a failure is detected, the corresponding LED lights up and the buzzer sounds an alarm. Designed with hot-swappable fan trays, any defective fan may be removed and replaced from the front panel even when the system is running, ensuring uninterrupted operation and reduced MTTR (Mean-Time-To-Repair). The PXIS-2630 chassis is the best alternative for all your PXI applications.

### Features

- Supports both 3U PXI and CompactPCI modules
- PXI Specifications Rev. 2.2 compliant
- Equipped with one system slot and seven PXI/CompactPCI peripheral slots
- Industrial-grade 400 W ATX power supply
- Hot-swappable fans design for easy replacement
- Filtered, forced air-cooling architecture
- Temperature, voltage, and fan monitoring LEDs



### Hot-swappable Fans for Easy Replacement

### Specifications

#### Power Supply

- Form factor: 400 W ATX AC power supply
- AC input: 100 to 240 VAC, 50 Hz to 60 Hz
- DC output: 400 W

Vdc	Minimum	Maximum
+5 V	2.5 A	35.0 A
+12 V	1.0 A	20.0 A
+3.3 V	1.0 A	28.0 A
-12 V	0.0 A	1.0 A

#### Cooling

- Fans: Five 80 mm x 80 mm x 15 mm ball-bearing fans in hot-swappable fan trays, 36 CFM/each

#### Physical

- Number of PXI slots: 8 (1 system slot + 7 peripheral slots)
- Dimensions: 483 mm x 178 mm x 258 mm (W x H x D) without handles
- Weight:
  - 11 kg (24.2 lbs)

#### Operating Environment

- Ambient temperature:
  - 0°C to 50°C
- Relative humidity: 10% to 90%, non-condensing

#### Storage Environment

- Ambient temperature:
  - -20°C to 70°C
- Relative humidity: 5% to 95%, non-condensing

#### Shock and Vibration

- Shock: 15 G<sub>peak-to-peak</sub>, 11 ms duration
- Random Vibration
  - Operating: 5 Hz to 500 Hz, 0.5 GRMS, each axis
  - Non-operating: 5 Hz to 500 Hz, 1.88 GRMS, each axis

#### Emissions Compliance

- EN 55022
- FCC Class A

#### CE Compliance

- Safety: EN 60950-1
- Immunity: EN 55024

### Recommended System Controller

	PXIS-2630
PXI-3900 series	√

### Ordering Information

- **PXIS-2630**  
8-Slot 3U PXI/CompactPCI Chassis with 400 W AC Power Supply
- **PXIS Spare Fan**  
PXIS Chassis Spare Fan for PXIS-2700 & PXIS-2600 Series