

# PCIe-8560/PXI-8565

## PCI Express-to-PXI/CompactPCI Expansion Kits



### Introduction

The PCI Express-to-PXI/CompactPCI expansion kit provides control of PXI/CompactPCI modules installed in a PXI/CompactPCI expansion system using the high-bandwidth PCI Express technology. With comprehensive hardware and software transparency, the expansion kit enables fast and convenient detection of any installed PXI/CompactPCI cards in the expansion system, without requiring additional drivers or software installation.



### Controlling PXI™/CompactPCI® with PCI Express®

The PCIe-8560 and PXI-8565 PCI Express-to-PXI/CompactPCI expansion kit provides additional PXI slots to the host computer by implementing a PCI Express-based control of PXI/CompactPCI modules. The technology consists of a PCIe-8560 card installed in the host computer, a shielded cable, and the expansion system with the 3U (Eurocard) PXI-8565 expansion module. The PCIe-8560 comes in a PCI Express x1 footprint and converts PCI Express signals to a PCI bridge that supports seven 32-bit/66 MHz PXI/CompactPCI modules.

### Features

- PCI Express-based control of PXI/CompactPCI
- High-speed PCI Express x1 interface
- Direct control of PXI/CompactPCI systems
- Supports 32-bit/66 MHz PCI™ interface
- Expansion distance of up to 7 meters (expansion cables at 1 M, 3 M, and 7 M)
- Comprehensive hardware and software transparency
- Compliant with
  - PCI Express® Base Specifications Rev. 1.0a
  - PXI™ Specifications Rev. 2.2
  - PCI-to-PCI Bridge Architecture Specifications Rev. 1.2
  - PCI™ Local Bus Specifications Rev. 3.0

### General Specifications

- Operating temperature: 0°C to 50°C
- Storage temperature: -20°C to 80°C
- Relative humidity: 10% to 90%, non-condensing

### Certification

- EMC/EMI: CE, FCC Class A

### Ordering Information

- **PCI Express-to-PXI Expansion Kit**  
Includes One PCIe-8560, One PXI-8565, and One ACL-EXPRESS-3 Cable
- **PCIe-8560**  
PCI Express-to-PXI Expansion Interface Card for host PC
- **PXI-8565**  
PCI Express-to-PXI Expansion Interface Card for 3U CompactPCI/PXI Chassis
- **PXI-8565/6U**  
PCI Express-to-PXI Expansion Interface Card for 6U CompactPCI/PXI Chassis
- **ACL-EXPRESS-1**  
High-speed Expansion Cable, 1 M
- **ACL-EXPRESS-3**  
High-speed Expansion Cable, 3 M
- **ACL-EXPRESS-7**  
High-speed Expansion Cable, 7 M

### Controlling 6U CompactPCI®/PXI™ Modules

For applications require controlling 6U PXI or CompactPCI modules through PCI Express, ADLINK provides the PXI-8565/6U, the 6U version of PXI-8565. The PXI-8565/6U provides the exact same features as PXI-8565 but in a 6U CompactPCI/PXI form factor. The product package includes one PCIe-8560 to plug into a host PC, one PXI-8565/6U for the remote 6U CompactPCI/PXI chassis, and one ACL-EXPRESS-1/3/7 expansion cable.



PCIe-8560



PXI-8565



PXI-8565/6U

### Specifications

- | ■ PCIe-8560             | <ul style="list-style-type: none"> <li>• PCI Express Base Specifications Rev. 1.0a compliant</li> <li>• PCI Express x1 link with 250 MB/s data throughput</li> <li>• Extended distance of up to 7 meters</li> <li>• Dimension: Low-profile PCI Express card 69 mm (H) x 87 mm (W)</li> <li>• Power requirement:               <table border="1"> <thead> <tr> <th>Device</th> <th>+3.3 V</th> </tr> </thead> <tbody> <tr> <td>PCIe-8560</td> <td>210 mA (max)</td> </tr> </tbody> </table> </li> </ul>  | Device | +3.3 V | PCIe-8560             | 210 mA (max) |
|-------------------------|---|--------|--------|-----------------------|--------------|
| Device                  | +3.3 V  |        |        |                       |              |
| PCIe-8560               | 210 mA (max)  |        |        |                       |              |
| ■ PXI-8565, PXI-8565/6U | <ul style="list-style-type: none"> <li>• PXI™ Specifications Rev. 2.2 compliant</li> <li>• PCI-to-PCI Bridge Architecture Specifications Rev. 1.2 compliant</li> <li>• PCI™ Local Bus Specifications Rev. 3.0 compliant</li> <li>• Supports 32-bit/66 MHz PCI™ interface</li> <li>• Internal arbiter supports up to 7 external masters</li> <li>• Up to seven PCI clock/bus requests</li> <li>• Extended distance of up to 7 meters</li> <li>• Dimensions: PXI-8565: 175 mm (W) x 107 mm (H)<br/>PXI-8565/6U: 175 mm (W) x 233.35 mm (H)</li> <li>• Power requirement:               <table border="1"> <thead> <tr> <th>Device</th> <th>+3.3 V</th> </tr> </thead> <tbody> <tr> <td>PXI-8565, PXI-8565/6U</td> <td>720 mA</td> </tr> </tbody> </table> </li> </ul> | Device | +3.3 V | PXI-8565, PXI-8565/6U | 720 mA       |
| Device                  | +3.3 V  |        |        |                       |              |
| PXI-8565, PXI-8565/6U   | 720 mA  |        |        |                       |              |
| ■ ACL-EXPRESS-1/3/7     | <ul style="list-style-type: none"> <li>• Length: 1 M, 3 M, 7 M</li> </ul>   |        |        |                       |              |