

HDV62A/PXle-HDV62A

One Channel PCI Express®/PXI Express® HDMI Video & Audio Capture Cards



HDV62A



PXle-HDV62A



Introduction

ADLINK's HDV62A/PXle-HDV62A high definition video and audio capture cards enable single-card acquisition of full analog/digital video and digital audio signals. Featuring uncompressed full HD up to 1080p at 60 fps and 10-bit high-resolution ADC and HDCP support, the HDV62A/PXle-HDV62A deliver serious benefits and reduced TCO for applications requiring simultaneous capture from both video and audio sources, such as multimedia device testing and medical imaging.

The HDV62A/PXle-HDV62A not only deliver uncompressed high-definition video data from DVI or HDMI, but also provide an analog video decoder comprehensively supporting RGB, NTSC/PAL, S-video and YPbPr, with an integrated audio decoder for HDMI and S/PDIF capture, providing a highly integrated solution.

HDV62A I/O Bracket (Optional)

- ◆ D-SUB9 female for NTSC/PAL and S-Video
- ◆ BNC x3 for YPbPr



Features

- Uncompressed 1920 x 1080p, 60 fps video stream
- Support for NTSC/PAL, S-video, RGB and YPbPr video input
- Support for HDMI and DVI video input
- Support for HDMI, S/PDIF audio input
- 10-bit high resolution ADC
- Support for HDCP (High-Bandwidth Digital Content Protection)
- PCI Express® x4 interface
- PXI Express® specification Rev. 1.0 compliant (PXle-HDV62A only)
- Configurable EDID
- Direct SDK support

Applications

- Medical imaging
- HDMI video/audio testing
- Multimedia device testing

Software Support

- OS Information
Windows® 7/XP
- Software Compatibility
Microsoft® DirectX
LabVIEW™
- Software Recommendations
ViewCreatorPro™

Ordering Information

- **HDV62A**
1-CH PCI Express® HDMI video / audio capture card
- **PXle-HDV62A**
1-CH PXI Express® HDMI video / audio capture card

Optional Accessories

- **HDV62A I/O bracket**
YPbPr, S-video and NTSC/PAL I/O
- **DVI – DVI and VGA cable**
DVI-I to VGA and DVI-D cable
- **DB9F to S-Video & RCA**
D-sub to S-video and RCA cable

Specifications

■ Form Factor	HDV62A: PCI Express® x4 compliant	
	PXle-HDV62A: PXI Express® specification Rev. 1.0 compliant	
■ Video Input	Digital: DVI 1.0, HDMI 1.3	
	Analog: RGB, YPbPr, NTSC/PAL, S-video	
■ Video Input Format	HD: 720p@50 fps, 720p@60 fps 1080i@25 fps, 1080i@30 fps 1080p@25 fps, 1080p@30 fps 1080p@50 fps, 1080p@60 fps	
	SD: 720 x 576@25 fps PAL 720 x 486@30 fps NTSC	
	■ Pixel Output Format	RGB: 32-bit RGB*, 30-bit RGB*, 24-bit RGB YUV: 24-bit 4:4:4 YCbCr 16-bit 4:2:2 YCbCr
		Monochrome: 8-bit Y
■ Audio Input	S/PDIF, HDMI	
■ Frame Buffer	DDR2, 512 MB	
■ Connectors	DVI: DVI-D, HDMI & RGB with sync input	
	D-SUB on I/O Bracket : NTSC/PAL, S-Video (HDV62A only)	
	BNC on I/O Bracket: YPbPr (HDV62A only)	
	Toslink & RCA: S/PDIF	
■ Operating Environment	Temperature: 0 to 55°C (32°F to 131°F)	
	Humidity: 5% to 90% RHNC	
■ Storage Environment	Temperature: 0 to 70°C (32°F to 158°F)	
	Humidity: 0 to 95% RHNC	
■ Power Requirements	+12 V max @ 0.5 A, +3.3 V max @ 2 A	
■ Dimensions (not including connectors)	PCIe version: 174.62 x 111.15 mm (W x L) (6.81" x 4.33")	
	PXle version: 174.62 x 111.15 mm (W x L) (6.81" x 4.33")	
■ Slot Requirement	2 peripheral slots (HDV62A w/I/O bracket, PXle-HDV62A)	

*Some computers may experience minor (10% or less) reduction of fps performance when 32-bit or 30-bit RGB output settings are in effect