

PCI-D64HU

Universal PCI, 40 MB/s High-speed 32-channel DI and 32-channel DO Board



Features

- Universal PCI (3.3 V/5 V) Interface
- 32-channel, 5 V/TTL Digital Output
- Data Transfer Rate up to 40 MB/s for each DMA Channel
- Onboard 1 k/2 k DWORD FIFO for DI/DO, respectively
- DO FIFO Supports Ring Buffer Mode
- No Bus Loading in Repetitive Pattern Generation Applications
- 32-channel, 5 V/TTL Digital Input
- 2-channel Bus Mastering Scatter/Gather
- 8-channel Optically-isolated Digital Input
- Data Transfer Modes:
 - Direct Program Control, Internal Timer Pacer
 - External Clock (DI only), Handshaking

Introduction

The PCI-D64HU is a high-speed digital I/O card containing 32 Digital Input channels and 32 Digital Output channels. The high-performance design makes this card perfect for high-speed data transfer and pattern generation applications.

The PCI-D64HU performs high-speed data transfer using a bus-mastering DMA via the 32-bit PCI bus, with a maximum data transfer rate of up to 40 MB per second. A variety of digital I/O transfer modes are supported, including direct programmed I/O control, timer pacer control, external clock mode and handshaking mode.

The PCI-D64HU also features a programmable digital filter for all input signals, including handshaking and trigger signals. The PCI-D64HU is a reliable and cost-effective interface that can be used to control any high-speed peripherals connected to your computer system.

Pin Assignments

Pin Assignment	Terminal No.	Pin Assignment
DI_0	01	20 DO_0
DI_1	02	21 DO_1
DI_2	03	22 DO_2
DI_3	04	23 DO_3
DI_4	05	24 DO_4
DI_5	06	25 DO_5
DI_6	07	26 DO_6
DI_7	08	27 DO_7
DI_8	09	28 DO_8
DI_9	10	29 DO_9
DI_10	11	30 DO_10
DI_11	12	31 DO_11
DI_12	13	32 DO_12
DI_13	14	33 DO_13
DI_14	15	34 DO_14
DI_15	16	35 DO_15
+5 V	17	36 GND
I_ACK	18	37 I_TRG
I_REQ	19	

Pin Assignment	Terminal No.	Pin Assignment
DI_16	01	02 DO_16
DI_17	03	04 DO_17
DI_18	05	06 DO_18
DI_19	07	08 DO_19
DI_20	09	10 DO_20
DI_21	11	12 DO_21
DI_22	13	14 DO_22
DI_23	15	16 DO_23
DI_24	17	18 DO_24
DI_25	19	20 DO_25
DI_26	21	22 DO_26
DI_27	23	24 DO_27
DI_28	25	26 DO_28
DI_29	27	28 DO_29
DI_30	29	30 DO_30
DI_31	31	32 DO_31
+5 V	33	34 GND
O_ACK	35	36 O_TRG
O_REQ	37	38 N.C.
N.C.	39	40 N.C.

CON2

Software

Drivers

- 32-bit Windows 2000/XP/2003/2008/Vista/7/8

Sample Programs

- VB/VC/BCB Demo

Hardware Specifications

Digital Input	
Channels	32
Compatibility	5 V/TTL
Input Voltage	Logic 0: 0.8 V Max., Logic 1: 2.0 V Min.
Handshaking Signals	I_REQ Input , I_ACK Output , I_TRG Input
Digital Output	
Channels	32
Compatibility	5 V/TTL
Output Voltage	Logic 0: 0.55 V Max., Logic 1: 2.0 V Min.
Output Capability	Sink: 64 mA @ 0.55 V, Source: 32 mA @ 2.0 V
Handshaking Signals	O_REQ Output, O_ACK Input, O_TRG Output
Transfer Speed	40 MB/s (Max.) for DI and DO simultaneously
Timer/Counter	
Channels	3
Resolution	16-bit
Input Frequency	2.5 ~ 20 MHz
Timer 0	DI Clock Source
Timer 1	DO Clock Source
Timer 2	Base Clock for Timer 0 and Timer 1
Interrupts	
Sources	O_ACK, I_REQ, Timer 0, Timer 1 and Timer 2
Onboard FIFO	
Size	1 k DWORD (32-bit) for DI 2 k DWORD (32-bit) for DO
Size in Ring Buffer Mode	2 ~ 2 k DWORD (32-bit), DO only
General	
Bus Type	3.3 V/5 V Universal PCI, 32-bit, 33 MHz
Connectors	Female DB37 x 1, 40-pin Box Header x 1
Power Consumption	200 mA @ +5 V Typical (no output load)
Operating Temperature	0°C to +60°C
Humidity	5 to 85% RH, Non-condensing

Ordering Information

PCI-D64HU CR	Universal PCI, 40 MB/s High-speed 32-channel DI and 32-channel DO (RoHS). Includes one CA-4037W cable and two CA-4002 D-sub connectors.
--------------	---