

MTV-64G5HP Kamera ze zintegrowanym zoomem optycznym 22x

Dane techniczne:

| | | |
|---------------------------|--|--------------------------|
| MODEL NO. | MTV-64G5HP | |
| TV SYSTEM | PAL | |
| IMAGE SENSOR | 1/4-inch CCD Image Sensor | |
| CCD TOTAL PIXELS | 795 (H) x 596 (V) | |
| SCANNING SYSTEM | 625 lines, 50 fields/sec | |
| SYNC SYSTEM | Internal / VD-Lock | |
| MINIMUM ILLUMINATION | Legacy mode | 1.5 Lux (F1.6, 5600 °K) |
| | Star light Mode | 0.07 Lux (F1.6, 5600 °K) |
| RESOLUTION | 520 TVL | |
| S / N RATIO | 48dB (min) / 52dB (typ) (AGC OFF, r=1, APC OFF, Y-OUT) | |
| WHITE BALANCE | ATW / AWB / FIX (zero color rolling) | |
| WHITE BALANCE RANGE | 3200 ~ 9600 °K | |
| B.L.C. FUNCTION | Super BLC, 48 zone BLC | |
| GAMMA CORRECTION | 0.45 /1 | |
| AGC | AUTO (24dB max) | |
| ALC | AUTO / FIX | |
| IMAGE NEGATIVE | Select by OSD menu | |
| CROSS LINE | ON/OFF Select by OSD menu (position adj. by software) | |
| FREEZE FUNCTION | Alarm in trigger or Select by OSD | |
| ELECTRONIC SHUTTER | AES : 1/60 (1/50) ~ 1/120,000 sec. / MANUAL : 8 step | |
| LENS | 22X optical ZOOM LENS, F1.6~3.8, f=4.0~88mm | |
| MOTOR-ZOOM / FOCUS / IRIS | 500 000 times life | |
| ZOOM | 220X (22X optical 10Xdigital) | |
| FOCUS | Auto / Manual | |
| POSITION | 64 Position (Zoom, Focus) | |
| VIDEO OUTPUT | Composite & Y/C output 1.0Vp-p at 75 ohm | |
| CONTROL FUNCTION | RS-232C/RS-485 (selectable), OSD control | |
| OSD LANGUAGE SELECT | ENGLISH / CHINESS_Simp / JAPANESE | |
| COMMUNICATION BAUD RATE | 9600 bps | |
| OPERATION TEMPERATURE | -10 °C to 50 °C | |
| OPERATIONAL HUMIDITY | within 85% RH | |
| POWER SUPPLY | DC12V±1V / 3.6W(max) | |
| DIMENSIONS | 59mm(W) X 80mm(H) X 120mm (L) | |

Dimension (Unit : mm / ±0.5mm)

